


SELECTABLE LIGHTING : FLAT PANEL LAY-IN TROFFER


Specs subject to change




Selectable Panel Light




Selectable
Color Temp




Selectable
Power




Flicker Free




Glare Reducing
Diffuser



UL Listed



DLC Premium



0 - 10V
Dimmable

Product Description

RCA Flat Panel Lay-In lights now offer selectable white lighting with selectable power to enhance your lighting design. Perfect for the office, healthcare facilities, education, retail, hospitality and more. RCA Selectable Lighting offers four color temperatures and five power usage levels to choose from. Making RCA Selectable lighting our most versatile light yet. Sealed to prevent debris, dust and other foreign materials from getting into the light. With a slim edge design to eliminate light leakage and all covered by the RCA Advanced Replacement Warranty.

Performance Summary

Initial Delivered Lumens	2,800 - 7,000 Lumens
Selectable Power	20 W / 30 W / 40 W / 50 W
Selectable Color Temp.	3500 K / 4000 K / 5000 K
Operating Temp Range	- 25° C (- 14° F) up to + 40° C (+ 104° F)
Efficacy	Up to 140 Lumens Per Watt
Beam Angle	110° Degrees
Input Voltage	AC 120 - 277V, 50 - 60 Hz
CRI	Up to 86
L80 Lifetime	50,000 Hours at L ₈₀
Advanced Warranty	5 Year Advanced Exchange Warranty
Controls	0 - 10 V Dimmable

Ordering Information

Example: PS1A1TB1041

Product	Size	Model Number	Watts	CCT	Lumens	Efficacy	Beam Angle	Controls
			W	K	lm	lm/w		
Flat Panel Lay-In Troffer	2' x 2'	P2035TB1041	20	3500	2500	125 lm/w	110°	0 - 10 V Dimmer
		P2040TB1041		4000				
		P2050TB1041		5000				
		P3035TB1041	30	3500	3750	125 lm/w		
		P3040TB1041		4000				
		P3050TB1041		5000				
		P4035TB1041	40	3500	5000	125 lm/w		
		P4040TB1041		4000				
		P4050TB1041		5000				
Flat Panel Lay-In Troffer	2' x 4'	P3035TB1011	30	3500	4200	140 lm/w	110°	0 - 10 V Dimmer
		P3040TB1011		4000				
		P3050TB1011		5000				
		P4035TB1011	40	3500	5600	140 lm/w		
		P4040TB1011		4000				
		P4050TB1011		5000				
		P5035TB1011	50	3500	7000	140 lm/w		
		P5040TB1011		4000				
		P5050TB1011		5000				
Selectable Flat Panel Lay-In	2' x 2'	PS1A1TB1041	Selectable	Selectable	Up to 4600	140 lm/w	110°	0 - 10 V Dimmer
	2' x 4'	PS1A1TB1011			Up to 7000			